

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG

INCHES

ALUMINUM

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
ILT (INSIDE LID TIGHT)							
ILT030-030A-XXX/AL	0.876	0.876	0.500	0.250	0.050	0.078	0.032
ILT104-324A-XXX/AL	1.093	3.781	0.500	0.188	0.062	0.188	0.032
ILT124-124A-XXX/AL	1.670	1.670	0.375	0.281	0.032	0.156	0.040
ILT124-216A-XXX/AL	1.674	2.424	0.625	0.250	0.093	0.218	0.040
ILT124-216S-XXX/AL	1.710	2.460	1.687	0.250	0.093	0.250	0.040
ILT200-200A-XXX/AL	1.920	1.920	0.375	0.281	0.032	0.156	0.032
ILT200-216A-XXX/AL	1.900	2.400	0.437	0.312	0.062	0.140	0.050
ILT200-316A-XXX/AL	1.900	3.400	0.437	0.312	0.062	0.203	0.050
ILT200-316B-XXX/AL	1.900	3.400	0.750	0.312	0.620	0.218	0.050
ILT200-400A-XXX/AL	1.900	3.900	0.437	0.312	0.062	0.203	0.050
ILT200-516A-XXX/AL	1.900	5.400	0.437	0.312	0.062	0.265	0.050
ILT200-516S-XXX/AL	1.900	5.400	0.750	0.312	0.125	0.265	0.050
ILT208-208A-XXX/AL	2.150	2.150	0.437	0.312	0.062	0.203	0.050
ILT208-504A-XXX/AL	2.150	5.025	0.437	0.312	0.062	0.140	0.050
ILT216-316A-XXX/AL	2.400	3.400	0.437	0.312	0.032	0.203	0.050
ILT216-400A-XXX/AL	2.400	3.900	0.437	0.312	0.062	0.140	0.050
ILT216-400C-XXX/AL	2.400	3.900	0.437	0.312	0.062	0.203	0.050
ILT216-500A-XXX/AL	2.374	4.874	0.437	0.312	0.062	0.219	0.050
ILT220.5-525A-XXX/AL	2.580	5.725	0.250	0.188	0.032	0.125	0.032
ILT224.5-500.5A-XXX/AL	2.735	5.015	0.500	0.250	0.032	0.156	0.050
ILT225-605.5A-XXX/AL	2.781	6.170	0.500	0.250	0.032	0.140	0.050
ILT227-607.5A-XXX/AL	2.780	6.170	0.250	0.250	0.032	0.125	0.032
ILT229-622A-XXX/AL	2.848	6.619	0.500	0.188	0.032	0.125	0.032
ILT300-316A-XXX/AL	2.874	3.374	0.500	0.312	0.062	0.188	0.063
ILT300-400A-XXX/AL	2.874	3.374	0.050	0.312	0.062	0.188	0.063
ILT300-416A-XXX/AL	2.874	4.374	0.500	0.312	0.062	0.125	0.063
ILT300-500A-XXX/AL	2.874	4.874	0.500	0.312	0.062	0.188	0.063
ILT300-600A-XXX/AL	2.874	5.874	0.500	0.312	0.062	0.188	0.063
ILT308-308A-XXX/AL	3.150	3.150	0.437	0.312	0.093	0.203	0.050
ILT310.5-328.5A-XXX/AL	3.327	3.890	0.500	0.250	0.032	0.312	0.040

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG ALUMINUM

INCHES

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
ILT (INSIDE LID TIGHT) CONTINUED...							
ILT316-508A-XXX/AL	3.400	5.150	0.437	0.312	0.062	0.203	0.050
ILT316-600A-XXX/AL	3.400	5.874	0.437	0.312	0.062	0.140	0.050
ILT316-724A-XXX/AL	3.400	7.650	0.437	0.312	0.062	0.219	0.050
ILT324-728A-XXX/AL	3.624	7.749	0.500	0.312	0.062	0.266	0.063
ILT400-400A-XXX/AL	3.875	3.875	0.500	0.250	0.062	0.250	0.063
ILT400-416A-XXX/AL	3.874	4.374	0.500	0.250	0.062	0.265	0.063
ILT400-500E-XXX/AL	3.920	4.920	1.000	0.375	0.040	0.108	0.040
ILT400-600A-XXX/AL	3.874	5.874	0.500	0.312	0.062	0.188	0.063
ILT400-616A-XXX/AL	3.874	6.374	0.500	0.312	0.062	0.265	0.063
ILT416-600A-XXX/AL	4.374	5.874	0.500	0.312	0.062	0.188	0.063
ILT423.5-531.5-XXX/AL	4.670	5.920	0.375	0.312	0.062	0.218	0.040
ILT424-600C-XXX/AL	4.670	5.920	0.375	0.218	0.032	0.188	0.040
ILT424-600D-XXX/AL	4.650	5.900	0.500	0.312	0.062	0.140	0.063
ILT424-620A-XXX/AL	4.624	6.499	0.500	0.312	0.062	0.188	0.063
ILT500-700A-XXX/AL	4.874	6.874	0.500	0.312	0.062	0.265	0.063
ILT505-517A-XXX/AL	5.172	5.532	0.625	0.250	0.062	0.248	0.050
ILT506-800A-XXX/AL	5.087	7.900	0.437	0.312	0.062	0.109	0.050
ILT600-800A-XXX/AL	5.874	7.874	0.500	0.312	0.062	0.265	0.063
ILT800-800A-XXX/AL	7.874	7.874	0.347	0.312	0.050	0.583	0.050
ILT800-900A-XXX/AL	7.874	8.874	0.500	0.312	0.032	0.188	0.063
ILT900-900A-XXX/AL	8.874	8.874	0.500	0.312	0.062	0.449	0.063

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG

INCHES

ALUMINUM

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
OLT (OUTSIDE LID TIGHT)							
OLT110-308A-XXX/AL	1.312	3.250	0.312	0.250	0.032	0.140	0.040
OLT112-504A-XXX/AL	1.375	5.125	0.375	0.281	0.032	0.218	0.040
OLT124-124A-XXX/AL	1.750	1.750	0.375	0.281	0.032	0.218	0.040
OLT124-200A-XXX/AL	1.750	2.000	0.375	0.281	0.032	0.218	0.040
OLT124-300C-XXX/AL	1.750	3.000	0.437	0.312	0.062	0.156	0.050
OLT200-300A-XXX/AL	2.000	3.000	0.437	0.312	0.062	0.218	0.050
OLT200-316A-XXX/AL	2.000	3.500	0.437	0.312	0.062	0.296	0.050
OLT200-400A-XXX/AL	2.000	4.000	0.437	0.312	0.062	0.296	0.050
OLT200-400C-XXX/AL	2.000	4.000	0.375	0.312	0.062	0.234	0.063
OLT207-530A-XXX/AL	2.218	5.937	0.500	0.312	0.062	0.250	0.063
OLT208-324A-XXX/AL	2.250	3.750	0.375	0.250	0.032	0.281	0.040
OLT210-412A-XXX/AL	2.312	4.375	0.375	0.250	0.032	0.109	0.040
OLT212-528A-XXX/AL	2.375	5.875	0.500	0.500	0.062	0.250	0.063
OLT216-400A-XXX/AL	2.500	4.000	0.437	0.312	0.062	0.203	0.050
OLT216-400C-XXX/AL	2.500	4.000	0.437	0.312	0.062	0.296	0.050
OLT216-409A-XXX/AL	2.500	4.281	1.000	0.250	0.062	0.218	0.032
OLT216-600A-XXX/AL	2.500	5.000	0.800	0.312	0.045	0.312	0.050
OLT220-426A-XXX/AL	2.625	4.812	0.500	0.300	0.063	0.213	0.050
OLT217-423A-XXX/AL	2.531	4.718	0.437	0.312	0.062	0.171	0.050
OLT229-405A-XXX/AL	2.906	4.156	0.437	0.312	0.050	0.296	0.050
OLT300-300E-XXX/AL	3.000	3.000	0.875	0.250	0.062	0.312	0.040
OLT300-316A-XXX/AL	3.000	3.500	0.500	0.312	0.062	0.312	0.063
OLT300-400A-XXX/AL	3.000	4.000	0.500	0.312	0.062	0.312	0.063
OLT300-400C-XXX/AL	3.000	4.000	0.500	0.312	0.062	0.188	0.063
OLT300-416A-XXX/AL	3.000	4.500	0.500	0.312	0.062	0.234	0.063
OLT300-500A-XXX/AL	3.000	5.000					0.063
OLT300-600A-XXX/AL	3.000	6.000	0.500	0.312	0.062	0.312	0.063
OLT300-700A-XXX/AL	3.000	7.000	0.375	0.312	0.032	0.302	0.040
OLT300-716A-XXX/AL	3.000	7.500	0.500	0.250	0.062	0.375	0.040
OLT308-408A-XXX/AL	3.250	4.250	0.437	0.312	0.046	0.234	0.050

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG

INCHES

ALUMINUM

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
OLT (OUTSIDE LID TIGHT) CONTINUED...							
OLT308-508A-XXX/AL	3.250	5.250	0.437	0.250	0.062	0.203	0.050
OLT316-316A-XXX/AL	3.500	3.500	0.500	0.312	0.032	0.312	0.063
OLT316-400A-XXX/AL	3.500	4.000	0.500	0.312	0.062	0.312	0.063
OLT316-508A-XXX/AL	3.500	5.250	0.437	0.312	0.062	0.281	0.050
OLT316-600A-XXX/AL	3.500	6.000	0.437	0.312	0.062	0.234	0.050
OLT320C-XXX/AL	3.625	DIA.	0.562	0.250	0.032		0.032
OLT326-326A-XXX/AL	3.812	3.812	0.500	0.312	0.062	0.297	0.063
OLT400-500A-XXX/AL	4.000	5.000	0.500	0.312	0.062	0.312	0.063
OLT400-508A-XXX/AL	4.000	5.250	0.437	0.312	0.062	0.296	0.050
OLT400-600A-XXX/AL	4.000	6.000	0.500	0.312	0.062	0.312	0.063
OLT400-616A-XXX/AL	4.000	6.500	0.500	0.312	0.062	0.375	0.063
OLT400-800A-XXX/AL	4.000	8.000	0.500	0.312	0.062	0.375	0.063
OLT400-900A-XXX/AL	4.000	9.000	0.500	0.312	0.062	0.297	0.063
OLT408-408A-XXX/AL	4.250	4.250	0.750	0.312	0.062	0.359	0.063
OLT408-408E-XXX/AL	4.250	4.250	0.500	0.250	0.062	0.234	0.050
OLT409-801A-XXX/AL	4.281	8.031	0.500	0.375	0.032	0.375	0.050
OLT410-700A-XXX/AL	4.312	7.000	0.500	0.312	0.062	0.328	0.050
OLT412-500A-XXX/AL	4.375	5.000	0.375	0.281	0.032	0.281	0.040
OLT412-516A-XXX/AL	4.375	5.500	0.437	0.312	0.062	0.296	0.050
OLT412-612A-XXX/AL	4.375	6.375	0.500	0.250	0.062	0.312	0.063
OLT416-416A-XXX/AL	4.500	4.500	0.500	0.312	0.062	0.360	0.063
OLT416-600A-XXX/AL	4.500	6.000	0.500	0.312	0.062	0.312	0.063
OLT416-716A-XXX/AL	4.500	7.500	0.500	0.312	0.062	0.250	0.063
OLT424-1024-XXX/AL	4.750	10.750	0.500	0.312	0.062	0.420	0.063
OLT424-620A-XXX/AL	4.750	6.625	0.500	0.312	0.062	0.312	0.063
OLT500-500A-XXX/AL	5.000	5.000	0.500	0.312	0.062	0.375	0.063
OLT500-600A-XXX/AL	5.000	6.000	0.500	0.500	0.062	0.375	0.063
OLT500-700A-XXX/AL	5.000	7.000	0.500	0.312	0.062	0.375	0.063
OLT500-700B-XXX/AL	5.000	7.000	0.500	0.312	0.125	0.375	0.063
OLT500-800A-XXX/AL	5.000	8.000	0.500	0.312	0.062	0.300	0.063

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG ALUMINUM

INCHES

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
OLT (OUTSIDE LID TIGHT) CONTINUED...							
OLT506-800A-XXX/AL	5.187	8.000	0.437	0.312	0.062	0.206	0.050
OLT514.2-818.4-XXX/AL	5.443	8.575	0.500	0.250	0.187	0.250	0.063
OLT516-516A-XXX/AL	5.500	5.500	0.500	0.312	0.062	0.375	0.063
OLT516-516E-XXX/AL	5.500	5.500	0.500	0.312	0.062	0.421	0.063
OLT516-800A-XXX/AL	5.500	8.000	0.500	0.312	0.062	0.312	0.063
OLT518-928C-XXX/AL	5.562	9.875	0.500	0.312	0.062	0.156	0.063
OLT524-624A-XXX/AL	5.750	6.750	0.500	0.312	0.062	0.359	0.063
OLT600-700A-XXX/AL	6.000	7.000	0.500	0.312	0.062	0.375	0.063
OLT600-800A-XXX/AL	6.000	8.000	0.500	0.312	0.062	0.312	0.063
OLT600-800B-XXX/AL	6.000	8.000	0.500	0.312	0.032	0.375	0.063
OLT600-900A-XXX/AL	6.000	9.000	0.500	0.312	0.062	0.375	0.063
OLT600-900C-XXX/AL	6.000	9.000	0.500	0.500	0.125	0.570	0.090
OLT616-912A-XXX/AL	6.500	9.380	0.500	0.312	0.062	0.531	0.063
OLT700-800A-XXX/AL	7.000	8.000	0.500	0.312	0.062	0.375	0.063
OLT700-900A-XXX/AL	7.000	9.000	0.500	0.312	0.062	0.500	0.063
OLT906-1308A-XXX-AL	9.187	13.250	0.500	0.312	0.062	0.687	0.063
OLT912-1400A-XXX/AL	9.375	14.000	0.375	0.250	0.062	0.468	0.050

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG ALUMINUM

INCHES

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
OLL (OUTSIDE LID LOOSE)							
OLL216-400E-XXX/AL	2.630	4.122	1.000	0.418	0.090	0.312	0.050
OLL300-300E-XXX/AL	3.065	3.065	0.875	0.250	0.062	0.312	0.040
OLL300-500A-XXX/AL	3.035	5.035	0.500	0.312	0.062	0.312	0.063
OLL300-627.8-XXX/AL	3.156	7.036	0.500	0.312	0.060	0.310	0.063
OLL324-500A-XXX/AL	3.780	5.030	0.500	0.312	0.062	0.562	0.063
OLL400-600A-XXX/AL	4.065	6.065	0.500	0.300	0.050	0.290	0.050
OLL400-700A-XXX/AL	4.065	7.065	0.500	0.312	0.062	0.406	0.063
OLL400-700B-XXX/AL	4.060	7.060	0.500	0.312	0.062	0.343	0.063
OLL408-408E-XXX/AL	4.302	4.302	0.500	0.250	0.062	0.230	0.050
OLL408-522A-XXX/AL	4.378	5.853	0.500	0.418	0.062	0.618	0.050
OLL428-616A-XXX/AL	4.910	6.535	0.500	0.312	0.062	0.250	0.063
OLL500-716C-XXX/AL	5.025	7.525	0.437	0.312	0.062	0.125	0.050
OLL516-516E-XXX/AL	5.525	5.525	0.500	0.312	0.062	0.343	0.063
OLL600-1200A-XXX/AL	6.040	12.040	0.500	0.312	0.062	0.375	0.063
OLL600-700A-XXX/AL	6.065	7.065	0.500	0.312	0.062	0.375	0.063
OLL600-900A-XXX/AL	6.065	9.065	0.500	0.300	0.050	0.406	0.050
OLL900-1200A-XXX/AL	9.030	12.020	0.500	TBA	0.090	0.230	0.050
OLL1000-1600-XXX/AL	10.000	16.000	0.625	0.250	0.062	1.000	0.090

ALUMINUM (AL) COVERS/LIDS

NORPIN COVERS ILT, OLT, OLL, OLG ALUMINUM

INCHES

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
OLG (OUTSIDE LID GASKET)							
OLG130-300A-XXX/AL	2.085	4.085	0.375	0.281	0.032	0.296	0.040
OLG224-416A-XXX/AL	2.995	5.644	0.437	0.312	0.062	0.312	0.050
OLG304-424A-XXX/AL	3.281	4.900	0.437	0.312	0.062	0.330	0.050
OLG316-508A-XXX/AL	3.620	5.370	0.500	0.310	0.060	0.280	0.063
OLG400-400A-XXX/AL	4.282	4.282	0.500	0.500	0.062	0.469	0.063
OLG400-508A-XXX/AL	4.160	5.410	0.437	0.312	0.062	0.250	0.050
OLG415.5-731.5-XXX/AL	4.625	8.125	0.437	0.213	0.062	0.140	0.050

PART NUMBER	WIDTH	LENGTH	TRIM HEIGHT MAXIMUM	TRIM HEIGHT MINIMUM	BOTTOM RADIUS	SIDE RADIUS	BLANK THICKNESS
ILL (INSIDE LID LOOSE)							
ILL112.5-301A	2.883	1.258	0.505	?	0.218	0.218	0.050